



PERSONAL
COMPUTERS



SMALL
COMPUTERS
NETWORK

critical
POWER SUPPLIES

iDialog / iDialog Plus

400-800 VA / 400-1600 VA single-phase

iDialog / iDialog Plus 400-800 VA / 400-1600 VA




The iDialog UPS has been designed to protect PCs and critical peripherals in home and small office environments. iDialog is easy to install and provides powerful, economic protection for:

- IT equipment including PCs, Media Centers, PoE, VoIP and other such peripherals
- TVs, Home Cinemas, Satellite and Digital Terrestrial receivers, DVD readers and writers
- Modems and xDSL routers
- Small household appliances

CHARACTERISTICS

- Maximum power protection with PowerShield³ UPS monitoring and shutdown software available for free download from our website www.riello-ups.com
- Suitable for installation on PCs running Windows 2008, Vista, 2003, XP; Linux, Mac OSX and the Sun Solaris operating system.
- Compact dimensions and ergonomic design: iDialog can be placed on a desk top or other convenient location, with easy to access connections and informative front panel.

- Front panel LCD display (Plus version only) providing status, load and battery information and LEDs (standard version).
- Silent running: iDialog can be used to protect other sensitive electronic devices including Home Cinemas, CD Writers, DVD players, Satellite and Digital Terrestrial receivers.



MODELS	ID 40	ID 60	ID 80	IDP 40	IDP 60	IDP 80	IDP 110	IDP 160	
POWER	400VA/240W	600VA/360W	800VA/480W	400VA/240W	600VA/360W	800VA/480W	1100VA/660W	1600VA/960W	
INPUT									
Rated voltage	220-240 Vac								
Voltage range	230 Vac (+20/-25%)								
Frequency	50/60 Hz auto sensing								
OUTPUT									
Voltage on mains operation	230 Vac (+/- 15%)								
Voltage on battery operation	230 Vac (+/- 10%)								
Frequency on battery operation	50 or 60 Hz (+/- 1%)								
BATTERIES									
Type	VRLA AGM Maintenance-free lead-acid								
Recharge time	6-8 h								
ENVIRONMENTAL									
Weight (kg)	3			3.2			3.4	6.6	7
Dimensions (HxWxD) (mm)	192 x 90 x 232						275 x 97x 315		
Tel/Modem protection	RJ11/45 connectors								
Communication	-			USB					
Output sockets	4 IEC		4 IEC or 3 Schuko/Italian or 3 french			6 IEC or 4 Schuko/Italian or 4 french			
Compliance	EN 62040-1-1 and Directive 2006/95/EC; EN 62040-3 EN 62040-2 and Directive 2004/108 EC								
Operating temperature	0°C ÷ +40°C								
Colour	Dark grey RAL 7016								
Altitude and relative humidity	6000 meters max. elevation, < 95% non condensing								
Accessories provided	2 output supply cables (IEC version), 1 USB cable (plus version), user guide								

