

Product data sheet

Characteristics

VDIP184646020

Actassi CL-MNC6 Patchcord F/UTP 4P Cat6
300MHz LSZH 2m Grey



Main

| | |
|-----------------------|--|
| Range | Actassi |
| Product | Patch cord |
| Product compatibility | Coloured clips blue Coloured clips yellow Coloured clips green Coloured clips red |
| Performance | 6 |
| Colour | Grey patchcord |

Complementary

| | |
|----------------------------|--|
| Provided equipment | Coloured clips red Coloured clips green Coloured clips grey |
| Cable shielding type | F/UTP |
| Communication network type | 10GBASE-T |
| Transmission frequency | 300 MHz |
| Input impedance | 100 Ohm |
| Connector type | RJ45 |
| Material | PE (polyethylene) wire insulation Solid bare copper conductor |
| Standards | ISO/IEC 11801:2011 Ed.2.2 EN 50173 Ed.3 EIA/TIA-568-C.2 IEC 61935-2 |
| Product certifications | Delta |
| Quantity per set | 1 |
| Cable length | 2 m |

Environment

| | |
|--|--------------------------------------|
| Environmental characteristic | LSZH (low smoke zero halogen) jacket |
| Temperature range | -20...60 °C |
| Ambient air temperature for storage | -20...60 °C |
| Ambient air temperature for installation | 0...50 °C |
| Temperature resistance | 60 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1144 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |